

AMP SERIES

PORTABLE TYPE AERIAL WORK PLATFORM

Mantall®



Standard Features

- Aluminum Platform Basket
- Polyurethane Non-mark tires
- Leverage Ro-Ro device
- Lifting ears
- Two controls: Platform Control and Ground Control
- Lower Beeper warning
- Tilt Device (only for AMP40)
- Emergency Lower Down
- Outrigger Storage Frame
- Maintenance-free battery

Options Features

- Door Type Standard/narrow/wide Platform
- Fiber Glass Platform
- Goods collection platform
- Narrow/Rough Ground Chassis
- DC Power
- Tool Box
- Platform Positioning Laser light
- Fluorescent Tubes Box
- Working Flashing Beacon
- Top Limit Protection Auto-stop device
- Equipment Protection cover

MODEL	AMP20	AMP26	AMP32	AMP40
Working height max H1	8.0 m	10.0 m	12.0 m	14.0 m
Platform height max H2	6.0 m	8.0 m	10.0 m	12.0 m
Lift capacity	159 kg			120 kg
Basket Size B x C	0.69 x 0.68 m			
Stowed Size E x F x D	1.27x0.74x1.97m	1.36x0.78x1.97m	1.42x0.78x1.97m	1.46x0.78x2.76m
Height, tilted back M	/	/	/	1.98m
Length, tilted back J	/	/	/	2.87m
Outrigger footprint I x K	1.77x1.49m		1.99x1.72m	2.27x1.98m
Wall access front/side H x G	0.18/0.45m	0.18/0.45m	0.23/0.55m	0.42/0.65m
Power source (AC/DC)	220V/110V/12V	220V/110V/12V	220V/110V/12V	220V/110V/12V
Weight (AC/DC)	355 / 405 kg	400 / 440 kg	427 / 477 kg	548 / 595 kg

